



## Labor-free automation with feeding, laminating and trimming at the touch of a button!



Adjustable trim for full encapsulation or precise fl ush cut

Green Button Operation: touch the button and walk away for labor-free, fully

trimmed and

## **Features**

- Small foot print less than 4 sq. ft.
- Table Top or optional stand with locking roller casters
- 115 Volt, 15 amp service with economy mode
- · Ultra quick warm up of less than 5 minutes
- · Virtually unattended operation
- Digital Sheet sizes:

- · Laminates copy paper up to 100lb cover stock
- · Automatic two side lamination or short one side work
- Adjustable Automatic Flush or Sealed edge trim
- 1 year parts and labor warranty

## **Exclusive A.S.A.P Roll Film**

- Perfect for digital print technology
- Anti-static properties

## **ALM 3230 Specifications**

Model	ALM 3230
Laminating Speed	Fixed speed at 40"/min.
Temperature Range	170-270°F
Warm-Up Time	Approximately 5 minutes
Film Thickness	1.5 mil, 3 mil, 5 mil A.S.A.P. film
Sheet Thickness	20lb bond - 100lb cover
Paper Feeding Capacity	100 Sheets, Adjustable Guide
Standard Paper Sizes	Letter Paper Size: 8½" x 11" Tabloid Paper Size: 11" x 17" Digital Paper Size: 12" x 18" Paper: Paper Size: 13" x 19"
Power Consumption	900W
Power Supply	AC 120V (60Hz)
Net Weight Laminator:	100 Lbs.
Net Weight Stand:	48.5 Lbs.

