

Triumph 5260 & 6660 Programmable Hydraulic Cutters

VRCUT[™] Ready TRIUMPH[®]

With VRCut Ready Triumph Cutters, operators of any experience level can use cutters accurately and efficiently without lengthy training or ramp up programs, allowing businesses to increase operation speed and efficiency while reducing operating costs and waste.

Comprehensive SCS™ safety package: patented EASY CUT electronic blade activation bars for true two-hand operation; IR light beam safety curtain on front table; safety cover on rear table; main switch and safety lock with key; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade and clamp return from every position; disc brake for instant blade stop; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine; blade and cutting stick can be changed without removing covers.

Ergonomic, 37 inch working height. Electric blade and clamp drive. Electric back gauge drive with touchpad for easy programming. Digital measurement display (cm or inches) with multilingual operator guidance, accurate to 1/10 mm or 1/100 inch. Stores 99 programs with up to 99 steps in each (up to 15 repeat cuts can be integrated as a single step). Pre-programmed for standard paper sizes. Memory key for repeat cuts. Automatic SET function for reference measurement and EJECT function for pushing out paper. Self-diagnostic system with error indication on display. Electronic back gauge control with variable speed control for manual back gauge setting. Bright, LED optical cutting line. 3-step, LED front table illumination. Adjustable, spindle guided back gauge with narrow separations and plastic gliders. Dual side guides on front and rear tables. High quality, German steel blade. Solid steel blade carrier and adjustable blade guides. All-metal construction. Includes stand with storage shelf, easy-access tool holder, and paper blocking tool. Optional side tables increase work surface. UL and C UL approved.



Triumph 6660
Programmable Cutter



(Not shown: Triumph 5260)

TRIUMPH 5260 Specifications	
Cutting width	20-3/8"
Cutting height	3"
Narrow cut	1-3/8"
Length behind blade	20-3/8"

TRIUMPH 6660 Specifications	
Cutting width	25-1/2"
Cutting height	3"
Narrow cut	1"
Length behind blade	24"