

# Triumph 5560/5560LT & 7260 Programmable Hydraulic Cutters

**VR*CUT* Ready TRIUMPH**

*With VR*CUT* Ready Triumph Cutters, operators of any experience level can use cutters accurately and efficiently without lengthy training or ramp up programs, allowing businesses to increase operation speed and efficiency while reducing operating costs and waste.*

Comprehensive SCS™ safety package: patented EASY CUT electronic blade activation bars for true two-hand operation; IR light beam safety curtain on front table; safety cover on rear table; main switch and safety lock with key; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade and clamp return from every position; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine; blade and cutting stick can be changed without removing covers.

Foot pedal for pre-clamping. Electric back gauge drive with touchpad control module for easy programming. Digital measurement display (cm or inches) with multilingual operator guidance, accurate to 1/10 mm or 1/100 inch. Stores 99 programs with up to 99 steps in each (up to 15 repeat cuts can be integrated as a single step). Pre-programmed for standard paper sizes. Memory keys for repeat cuts. Automatic SET function for reference measurement and paper EJECT function. Integrated calculator. Self-diagnostic system with error indication on display. Electronic back gauge control with variable speed control for manual back gauge setting. False clamp plate. Bright, LED optical cutting line. High quality, German HSS blade. Precision swing cut blade movement. All-metal construction. Includes easy-access tool holder and paper blocking tool. Optional side tables increase work surface. UL and C UL approved.



Triumph 5560  
Programmable  
Hydraulic Cutter



(Not shown: Triumph 7260)

### TRIUMPH 5560/5560LT Specifications

Cutting width	21-5/8"
Cutting height	3-3/4"
Narrow cut	1-1/4"
Length behind blade	22-7/16"

- Hydraulic blade drive
- Fully adjustable clamp pressure between 1,900 and 3,800 psi
- TRIUMPH 5560 LT equipped with front and rear air tables (by special order only)

### TRIUMPH 7260 Specifications

Cutting width	28"
Cutting height	3"
Narrow cut	3/4"
Length behind blade	28"

- Electric blade drive
- Fully adjustable clamp pressure between 550 and 4,400 psi
- Standard air tables (front and rear)