

DESTROYIT® 3104

Wide, 12" feed opening and a sturdy single phase motor rated for continuous operation. Shred volume is a hefty 32 gallons.



A SOLID STEEL CUTTING SHAFTS
High grade, hardened steel cutting shafts are milled in our Balingen factory and warranted for life. *

B ECC CAPACITY INDICATOR
Patented Electronic Capacity Control (ECC) indicator monitors sheet capacity levels during operation to prevent jams.

C EASY SWITCH
Multifunction control element uses optical signals to indicate the operational status, and functions as an emergency stop switch.

D ENVIRONMENTALLY FRIENDLY BIN
Durable, lightweight shred bins can be used with or without disposable bags.

*Super micro-cut shafts are covered by a 1 year warranty.

DESTROYIT® 3104

Comprehensive SPS safety package: Easy Switch control element uses illuminated color codes and symbols to indicate operational status and functions as an emergency stop switch; patented, electronically controlled, transparent safety shield in the feed opening; automatic power cut-off when cabinet is opened or shred bin is full; automatic reverse and power cut-off when overfed; double protection against overheating; Zero Energy Consumption sleep mode cuts off power supply after 30 minutes of inactivity.

Automatic start and stop controlled by photo cell. Patented Electronic Capacity Control (ECC) indicator prevents jams by monitoring sheet capacity levels during operation. High quality, hardened steel cutting shafts take staples, paper clips, and credit cards (strip-cut and 4 x 40 cross-cut models take CDs / DVDs). Lifetime warranty on the cutting shafts. Quiet and powerful single phase motor rated for continuous operation. Sturdy Twin Drive System with fully enclosed gear box housing. High quality wooden cabinet mounted on casters. Convenient, environmentally friendly shred bin does not require disposable shred bags.

Security level P-2	.187" strip-cut (4 mm)
--------------------	------------------------

Sheet capacity	27 - 30*
----------------	----------

Security level P-4	.187" x 1.5" cross-cut (4 x 40 mm)
--------------------	------------------------------------

Sheet capacity	22 - 25*
----------------	----------

Security level P-5	.093" x .625" cross-cut (2 x 15 mm)
--------------------	-------------------------------------

Sheet capacity	14 - 17*
----------------	----------

* Sheet Capacity is based on 70 gsm paper, and are normally only achievable in ideal situations, so heavier duty paper will shred less sheets. In many cases the capacities quoted are theoretical as conditions vary and are dependent on operator usage, age and condition of machines, how regularly cutters are oiled, type and quality of paper etc. so realistic throughputs can be as low as half that of the theoretical capacities quoted.

Specifications:

Shred volume	32 gallons
--------------	------------

Feed opening	12"
--------------	-----

Electrical requirements	115 volts
-------------------------	-----------

Maximum horsepower	1
--------------------	---

Dimensions (D x W x H)	18.5" x 21" x 36.5"
------------------------	---------------------

Shipping weight	132 lbs.
-----------------	----------



BindRite
www.bindrite.com