

GROMMETSNIPE™

Commercial-grade alignment fixture for precision grommet-to-edge spacing up to 3" and grommet-to-grommet spacing from 2" to 24" center-to-center. Compatible with CSTEP-2 and CS-TIDY-41

FEATURES

- Telescoping, smooth, roller bearing horizontal ruler
- Rigid adjustable edge-alignment fence
- English-metric graduations
- Knurled thumbscrew for locking the desired adjustment



EYELED™

Bright red LED positioning dot for aligning material to a printed registration mark including adjustable mounting bracket, DC battery pack and plug-in AC adaptor. Compatible with CSTEP-2 and CS-TIDY-41

FEATURES

- Left or right adjustable mount
- Very low energy consumption
- 100s of hours on 2 AA batteries
- No health risks from use of lasers



FILTER-REGULATOR-LUBRICATOR

Reduce house air to machine-safe, project appropriate pressure. Prevent damage from air-line moisture and debris

FEATURES

- Custom stainless steel mounting bracket
- Air pressure quick release slide valve
- Swiveling 1/4" NTP inlet with 8 mm adaptor



WORK TABLE

Custom-fit design exclusive to the CS-TIDY machines with a well-balanced ergonomic configuration, powder coated steel construction, telescoping legs & leveling feet.

FEATURES

- Recessed grommet storage bins
- Table height adjustable for 25" - 33"
- 4 machine-to-table press positions
- Multi-position angled foot pedal mount



LOW PROFILE MOBILE CART

Wheel the CS-TIDY grommet machine around large projects rather than moving the material through a stationary press

FEATURES

- Heavy-duty locking casters
- Grommet & washer storage bins
- Durable powder-coated steel
- Lightweight with easy-lift handles

