



Gfp

Graphic Finishing
partners

Where Finishing Comes First.

Gfp 865DH-4RS

Versatile Dual Heat Laminator

For finishing professionals who need versatility, quality, and economy in one machine, the Gfp 865DH-4RS delivers. Turn out thermal encapsulation with low melt films (1.5-10mil), PSA lamination, and mounting jobs quickly and easily.

ULTIMATE FLEXIBILITY

Dual Heat for Thermal & Cold Apps

MAXIMIZE PRODUCTIVITY

Inline Rotary Slitters

FAST ROLL CHANGES

Front/Rear Swing-out Shafts

EASY LOADING

3" Quick-Grip Swing-out Shafts

INDUSTRIAL DESIGN

Years of maintenance-free service



Laminating • Mounting • Encapsulating

Our most flexible, cost-effective laminator yet

Spend less time on set-ups and changeovers with swing-out Quick-Grip supply shafts. Two front rewind shafts allow thermal encapsulation of prints from a roll.



- Labor Saving Swing-out Supply Shafts
- Drop-in Quick-Grip Rewind Shafts
- Photoelectric Eye for Operator Safety
- Independent Top and Bottom Heaters
- Web Clutch Adjustment for Output Quality
- Includes Rear Rewind with Rotary Slitters
- Swing-up Feed Table and 38" Output Height



Includes motorized rear rewind with rotary slitters for roll-to-roll applications.

Slitters not for use with thermal films.



Media alignment disks keep supply rolls from telescoping

Rugged Design
Professional Quality
Proven Performance
Economically Priced

865DH-4RS

APPLICATIONS

Signs
Posters
POP Displays
Trade Show Displays
Dry-erase Boards
Graphic Mounting
Photo Mounting
Floor Graphics
Window Graphics
Vehicle Graphics

cTUVus
Safety
Approval



Warranty:

2 year parts & labor.
Installation is included.

Laminating Width	65"
Roller Diameter	5"
Roller Gap	1"
Main Rollers	Silicone
Supply Roll Diameter(max)	16" Bottom, 8" op
Supply Shafts	3 (2 Swing-out)
Swing-out Shaft Maximum Weight	115 lbs.
Rear Rewind with Rotary Slitters (Not for use with thermal films.)	Included
Max. Temperature	266°F
Heat Method	Quartz Heater
Film Thickness	1.5 - 10mil
Laminating Speed	0-13 ft/min
Drive Motor	DC Geared Motor
Pressure Adjustment	Dual Hand Wheels
Roller Heating	Top & Bottom
Power Supply	240v 60HZ Single Phase 24A
Power Consumption	Max. 5760W
Dimensions	87" x 34" x 49"
Net Weight w/ stand	846 lbs.
Shipping Dimensions (L x W x H)	89" x 40" x 56" 1143 lbs.

Your local dealer is:

BindRite
www.bindrite.com



Gfp Graphic Finishing
partners

