# Phoenix 440-ML Mounting Laminator

The Phoenix™ 440-ML Mounting Laminator was designed to be a flexible and economical resource for producing signage & display materials. The top heated roller allows for thermal product applications while the release liner rewind makes it possible to easily work with pressure sensitive materials.

## KEY FEATURES:

- Five Roller Gap Settings
- Variable Speed Control
- Variable Temperature Control
- Quick-Grip Film Shafts
- Single Knob Tension Control
- Fold Down Rear Exit Tray
- Chain Driven Rewind
- Print Roll Hangers
- Print Feed Guides
- Print Hold Down Clamp
- Emergency Stop Button
- Photoelectric Eye for Safety
- Sleep & Auto-Off Energy Saver
- Stand with Locking Casters

## APPLICATIONS

- Signs
- Posters
- POP Displays
- Trade Show Displays
- Single-sided Lamination
- Mount Graphics
- Mount Photos
- Window Graphics
- Pre-mask
- Mounting Boards
- Pouch Boards
- PSA Film

| | | | |
|---|---|---|---|
| Maximum Width | 44" | Auto Sleep Function | 4 hours idle, turns heat off |
| Roller Diameter | 3.5" | Tension adjustment | Single Knob |
| Adjustable Speed | 0 - 5 feet per minute | Power Supply | 120v 12A |
| Temperature Range | 100° - 302° F | Power Consumption | 1440 W |
| Heating Method | Quartz heater | Foot Pedal / Stand | Included with unit |
| Film Weights | 1.5 - 5 mil | Dimensions, w/ rear deck up | 57" L x 37.75" D x 50" H |
| Gap / Pressure Settings | 0", 1/16", 1/8", 3/16" & 1/4" | Shipping Dimensions | 59.25" L x 35.5" W x 26.75" H |
| Supply Unwind / Rewind | Quick-Grip Top | Net / Shipping Weight | 264 lbs. / 395 lbs. |
| Auto Stand By | 3 hours idle, drop to 176° F | Warranty | 1-yr parts / 3 mos. labor & rollers |

## LAMINATING • MOUNTING • PRE-COAT BOARDS • PRE-MASK

**TOP ROLLER HEATED • EASY TO OPERATE • AFFORDABLE PRICE • SMALL FOOTPRINT • FLEXIBLE APPLICATIONS**

BindRite
www.bindrite.com