

# SP1360



## Specifications

|                                      |                                 |                                                                                                                                                                                |
|--------------------------------------|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Print Speed</b>                   | CMYK/Mono                       | 60 ppm COM 10 envelopes, 50 ppm Letter-size sheets, 27 ppm Tabloid sheets                                                                                                      |
| <b>Time to First Page</b>            | CMYK/Mono                       | Approx. 8 seconds                                                                                                                                                              |
| <b>Duty Cycle</b>                    | Printers                        | 300,000 pages max per month                                                                                                                                                    |
| <b>Print Quality</b>                 | Resolution                      | Up to 1200 x 1200 dpi; ProQ 1200 x 600 x 16 levels                                                                                                                             |
| <b>Memory</b>                        | RAM (Standard/Max)              | 2 GB                                                                                                                                                                           |
|                                      | Processor                       | 1.2 GHz ARM CPU                                                                                                                                                                |
| <b>Compatibility</b>                 | Printer Languages               | Adobe® PostScript 3™, PCL® 6, PCL 5c, XPS®                                                                                                                                     |
|                                      | Connectivity                    | High-speed USB 2.0, 10 Base-T/100 Base-TX/1000 Base-T Ethernet                                                                                                                 |
|                                      | Operating Systems               | Windows 10, Windows® 8, Windows 7, Windows Vista®, Windows XP, Windows Server 2012, Windows Server 2008, Windows Server 2008 R2, Windows Server 2003; Mac® OS 10.3.9 – 10.9    |
|                                      | Network Protocols               | TCP/IP, EtherTalk                                                                                                                                                              |
| <b>Color Features/<br/>Solutions</b> | Standard                        | PostScript® driver supports trapping; Embedded ICC Profile-based workflow; Simulations for SWOP, ISO Coated, Japan Color; PDF Direct Print; PS Gamma Adjust; and Color Correct |
| <b>Media Handling</b>                | Media Sizes                     | Trays 1 & 2: Up to 12.00" x 18.00"<br>Multi-purpose Tray: Min 2.52" x 3.50" up to 13.00" x 52.01"                                                                              |
|                                      | Media Weight                    | Trays 1 & 2 : 52 – 320 gsm<br>Multi-purpose Tray: 80 – 360 gsm                                                                                                                 |
| <b>Media Capacity</b>                | Multi-purpose Tray              | Up to 310 sheets                                                                                                                                                               |
|                                      | Trays 1 & 2                     | Up to 580 sheets each                                                                                                                                                          |
|                                      | High-Capacity Feeder (Optional) | Up to 1740 sheets (3 trays, 580 sheets each)                                                                                                                                   |
| <b>Media Output</b>                  | Face Down                       | Max 610 sheets                                                                                                                                                                 |
|                                      | Face Up                         | Max 300 sheets                                                                                                                                                                 |
| <b>Environmental</b>                 | Size (WxDxH)                    | 27.5" x 26.18" x 25.2" (699 mm x 665 mm x 640 mm)                                                                                                                              |
|                                      | Weight                          | 215.2 lb. (97.6 kg) including consumables                                                                                                                                      |
|                                      | Temperature/Humidity            | 50° – 90°F (10° – 32°C)/20% – 80%RH                                                                                                                                            |
|                                      | Power Consumption               | 115V 15A Active 1600W max./1100W avg.; Standby avg. 40W; PowerSave mode 30W or less; Sleep mode 4W or less; Auto Shutoff 0.4W or less.                                         |
|                                      | Noise Levels                    | Printer: Active 57dBA or less; Standby 34dBA or less;<br>PowerSave mode — Inaudible                                                                                            |
| <b>Warranty</b>                      | Limited                         | 1 year warranty                                                                                                                                                                |

- LED printheads control the amount of toner applied to each 1200-dpi dot, preserving fine image detail and maximizing color fidelity
- End user replaceable consumables ensures minimum down time
- Low total cost of ownership (TCO)
- Single pass color technology improves color registration for all paper types and weights
- Up to 50 ppm CMYK/Mono, and 60 ppm COM 10 envelopes