

New Model of the Full-Auto Laminator Series

Laminating Work Will Be Even Easier



Youtube




Revo Any

Pouch Laminator vs. Revo-Any: Key Differences in an Hour

Pouch Laminator

Stand by the machine "All the time"




General business laminators require constant supervision, making the process time-consuming and inefficient.

Full Auto Laminator

Revo-Any

Automated laminator processing



Place the paper on the tray and press start. Revo-Any laminates automatically, letting you focus on other tasks. Save time and boost productivity!

Anywhere

Compact size for any space.



Any Jobs

Simple operation for all tasks.



Set the paper, press start, and let it laminate.

Anyone

Easy setup for everyone.



Easy film reloading with a wide-open cover and film-cassette system.

Specifications

Warm-Up Time	Approx. 7 minutes (*1)
Max. Laminating Width	12"
Weight of Usable Paper	16 lbs. Bond to 42 lbs. Bond.
Laminating Film	2mil (197ft), 3mil (98ft), 5mil (82ft)
Laminating Speed	17.7"/min, 23.6"/min, 29.5"/min
Laminating Temperature	194°F - 248°F (Variable)
Power Supply	UL: 100-120VAC, 50/60Hz
Max. Power Consumption	600W
Body Size	W 24.8" (*2) x D 20.7" x H 11"
Body Weight	55lbs (Approx.)

*1) Warm-up time varies based on the operating environment and set temperature.

*2) Dimensions exclude the output tray.

Specifications and designs are subject to change without notice for product improvement.



Revō Any



Revō Office



Revō T14



Revō Flex




Max. Lamination Width	12inch	12inch	12inch	12.6inch
Film Thickness	2/3/5mil	2/3/5mil	2/3/5mil	1.5/3/5mil
Paper Size	SRA3/A3/A4/A5/B4/B5/Legal/Letter/Long Mode			
Side Trimming Function	x	x	x	○
Max. Lamination Speed	29.5inch per minute	39inch per minute	63inch per minute	78.7inch per minute
Lamination Temperature	194-248°F	194-248°F	194-248°F	176-284°F
Power Requirement	UL: 100V, 600W	UL: 100V, 1,000W	UL: 100V, 1,000W	UL: 100V, 1,000W
Mashine Size [W×D×H(inch)]	24.8"×20.7×112	26.8"×20×13.3	20.9"×35.5×16.5	51"×24"×42.5"
Warming Up Time	7 minutes ^{*4}	5 minutes ^{*4}	5 minutes ^{*4}	5 minutes ^{*4}

*1: Exclusive output tray *2: Exclusive up & Down lever *3: When the stand, feed tray, and other components are fully assembled *4: Changes may occur depending on the operating temperature and settings.

Film Cassette For Revo-Office

Save time by preparing a spare film cassette for easy reloading of films.



Stand (Optional)

<Compatible Models>
Revo-Any / Revo-Office / Revo-T14

Easily movable with casters, and allows storage of Revo films inside the stand.



www.lami-corporation.co.jp/english/series-lamirevo



Web site for
Revo series



www.lami-corporation.co.jp/english/series-lamirevo

the
BindRite™
dealer network