

# HLA-2301

## AUTOMATIC LAMINATOR

### High-Speed, Commercial-Grade, Fujipla Laminator!

The newest, commercial-grade Fujipla laminator by Dry-Lam has everything you know and love about the previous ALM line for automatic feeding, laminating, trimming, and stacking sheets, but is now faster and better with improved features and functionality! Laminating up to 68" per minute, it is 25% faster than the ALM3230.

**DRY-LAM**  
Preserve and protect what matters.

**FUJIPA**




Width: 13"


### New & Improved!



Simple-slide paper  
size adjustment



Improved film roll  
installation



Upgraded multi-  
thickness feed tray



Easy-to-use Color  
Screen & Controls

### Recommended Film\*

- ▶ DL-HLA38GLOSS 1.5 mil Gloss
- ▶ DL-HLA75GLOSS 3.0 mil Gloss
- ▶ DL-HLA75MATT 3.0 mil Matte
- ▶ DL-HLA125GLOSS 5.0 mil Gloss

\*Additional options available.  
Contact sales for more info.



## FEATURES

- ▶ **Zero waste mode** for reduced film scraps on border-cut sheets
- ▶ **Joint mode** with gap or no gap, for folded applications or multi-sheet prints
- ▶ **Ultra-quick warm-up** time of less than 5 minutes
- ▶ Automatic **single or double-sided** lamination
- ▶ **2 Automatic trim** options
  - Flush-cut: precise, micro-adjustable with  $\pm 5$ mm margin adjust
  - Border-cut: custom-sealed options with 4-sided trim uniformity
- ▶ Hands-free, **automatic feed** tray
- ▶ Includes **stand with waste basket** to collect scraps
- ▶ Simple operation with **specially encoded film** for auto settings

## NEW “EVERSTICK” FILM ROLLS

- ▶ **New and improved** HLA film designed for optimal operation of the HLA-2301\*
- ▶ **Strong adhesion** with no peeling or bubbling, even on flush-cut sheets
- ▶ Proprietary **chip-reading** design
- ▶ **Automatically sets** to the correct temperature for the film in use

\*Former ALM SAP film rolls are not compatible with the HLA-2301

Model	HLA-2301
Laminating Width	12.6"
Speed	84" per minute
Film Thickness	1.5 - 10 mil film (10 mil single-side only)
Paper Thickness	17lb - 100lb cover
Laminating Thickness	16 mil
Heat Type	Heated Rollers
Temperature Range	170 - 270°F
Warm-up Time	Less than 5 minutes
Paper Sizes	8.5"x5.5", 8.5"x11", 11"x17", 12"x18", 13"x19"
Paper Feed Capacity	200 Sheets
Trimming Methods	Flush cut or Border cut; Double cut, Single cut modes
Operation Panel	Color LCD Display
Power Supply	100-240 VAC, 50-60Hz
Dimensions (LxWxH)	48" x 23.5" x 44"
Weight	Laminator: 163 lbs