



XYRON[®] XM4400

COLD LAMINATOR



LAMINATE, BOND, WORK
LIKE A PRO.





XYRON® XM4400 COLD LAMINATOR

Instantly applies laminate, adhesive or both without heat to documents up to 42" wide.

FEATURES:



Quick Application

Specialty supplies allow for quick and easy application changes.



Maximum Versatility

Aggressive adhesive, coupled with high pressure rollers, improves both transfer and bonding qualities. Trim documents immediately after lamination and the laminate will not peel or lift.



Easy to Use

The take-up rollers allow for one-person operation.

Laminator Type	Cold
Maximum Substrate Width	42" (1066.8 mm)
Foot Switch	Yes
Film Type	Pressure Sensitive
Maximum Substrate Thickness (Nip)	.10" (2.54 mm)
Electric Requirements	110V @ 2 Amp (max)
Machine Dimensions	50.5" L x 11" W x 14.5" H (1270 mm x 279.4 mm x 368 mm)
Stand Dimensions	49.5" L x 22" W x 28" H (1257.3 mm x 558.8 mm x 711.2 mm)
Machine Weight	155 lbs. (70.30 kg)
Shipping Dimensions	65.5"W x 37.25"D x 30"H (1663.7mm x 946.15mm x 762mm)
Shipping Weight	202 lbs. (92 kg)
Warranty	1 Year

ITEM#	DESCRIPTION
4400-00-01	XYRON® XM4400 LAMINATOR
DL3800-300	XYRON 38" STANDARD LAMINATE REFILL FOR XM4400
DL3802-300	XYRON 38" THERMAL SENSITIVE LAMINATE REFILL FOR XM4400
DL4300-300	XYRON 42" THERMAL SENSITIVE LAMINATE REFILL FOR XM4400
LAT3801-300	XYRON 38" STANDARD LAMINATE/HIGH TACK ADHESIVE REFILL FOR XM4400
LAT4301-300	XYRON 42" STANDARD LAMINATE/HIGH TACK ADHESIVE REFILL FOR XM4400
AT4306-170	XYRON 42" REPOSITIONABLE ADHESIVE REFILL FOR XM4400

©2024 ACCO Brands. All rights reserved. All other trademarks are the property of their respective owners.