



SEAL® 65 EL COLD LAMINATOR



COLD
ROLL LAMINATOR

LAMINATES
UP TO 65" WIDE

DURABLE
UNIFRAME CONSTRUCTION



SEAL® 65 EL COLD LAMINATOR

Designed for ease-of-use and minimal maintenance on sturdy uni-frame construction, the 65 EL is ideal for creating professionally-finished wide format graphics. Includes comprehensive safety system with self checking eyes and emergency stops.

TUV SUD Certified in US/Canada

FEATURES:



Cold Lamination

Cold roll laminator capable of mounting and laminating pressure-sensitive graphics.



Maximum Versatility

Confidently finishes a variety of applications. Laminates graphics up to 65" wide at speeds up to 14'/minute. Manual nip adjustment up to 1" for handling of most substrates. Factory installed image guide and leveling feet help to ensure perfect alignment and flat lamination.



Easy to Use

Simplified controls and easy material loading, featuring auto-grip rollers, and flip-up in-feed table for fast webbing, ensure easy and efficient finishing. Auto-grip supply shaft storage kit and factory installed roll trough keep rolled prints in place.

Laminator Type	Cold
Maximum Substrate Width	65" (1651 mm)
Maximum Laminating Speed	14'/min. (4.25 m/min)
Foot Switch	Yes
Film Type	Pressure Sensitive
Core Diameter	3" (76 mm)
Maximum Substrate Thickness (Nip)	1" (25 mm)
Roller Pressure	3 lbs./in. (0.53 N/mm)
Auto-Grip Shafts	2
Maximum Roll Diameter	Unwind 8" (203 mm) Take-Up 6" (152 mm)
Maximum Film Weight	Unwind 85 lbs. (38.5 kg) Take-Up 35 lbs. (15.9 kg)
Electric Requirements	115VAC, 50/60Hz, 1A, 115W-NEMA 5-15 Plug
Machine Dimensions	48"H x 82.3"W x 24"D (1220 mm x 2090 mm x 610 mm)
Machine Weight	430 lbs. (195 kg)
Shipping Dimensions	61"H x 88"W x 30"D (1549 mm x 2235 mm x 762 mm)
Shipping Weight	544 lbs. (247 kg)
Warranty	2 Year Limited. Extended warranty options available

ITEM#	DESCRIPTION	PRICE
65659	SEAL® 65 EL LAMINATOR	\$