



SEAL® 65 PRO MD

LAMINATOR WITH
SLITTER ASSEMBLY



DUAL
IR QUARTZ HEATED ROLLERS

65 INCH
WIDE MOUNTING LAMINATOR

EASY
OPERATOR INTERFACE



SEAL® 65 PRO MD LAMINATOR WITH SLITTER ASSEMBLY

The SEAL® 65 Pro MD with slitter assembly is a high production, versatile laminator that can run both hot and cold applications. Its unmatched capability of running at speeds more than 15 feet per minute provide efficiency without sacrificing quality. Additionally, this laminator is designed with a sturdy uni-frame construction and features fully adjustable temperature, speed and pressure settings. Includes comprehensive safety system with self checking eyes and emergency stops.


TUV SUD Certified in US/Canada

FEATURES:



Hot and Cold Lamination

Dual IR Quartz heated rollers capable of running both hot and cold films. The rollers heat quickly to reduce set-up time and increase the thermal conductivity to maintain a more consistent, uniform temperature across the entire roll surface.



Maximum Versatility

65" working width to handle a wide range of media at a maximum operating speed of 15'/minute. 2" nip with precision pneumatic rollers for even speed and pressure to ensure smooth, wrinkle-free graphics. Easy handling with 4-auto-grip swing out supply shafts and bi-directional operation allows for efficient operating.



Easy to Use

Easy Operator Interface (EOI) with a touch screen, flip up in feed table for easy webbing, foot switch for hands free operation and self checking safety eyes for increased operator safety. Includes slitter assembly including 2 cutters and slitters factory installed.

Laminator Type	Thermal/Cold
Maximum Substrate Width	65" (1651 mm)
Maximum Laminating Speed	15'/min. (4.25 mm/min)
Foot Switch	Yes
Film Type	Thermal & Pressure Sensitive
Core Diameter	3" (76 mm)
Maximum Substrate Thickness (Nip)	2" (50 mm)
Maximum Roller Temperature	275F (135C)
Roller Heating	Dual (Top/Bottom)
Temperature Control	Top/Bottom
Auto-Grip Shafts	4 Supply/3 Drop In
Maximum Roll Diameter	Supply (4 positions) 12" (305 mm) / Take-Up (2 positions) 8" (200 mm) / Combi (2 positions) 10" (254 mm)
Maximum Roll Weight	120 lbs. (54 kg)
Electric Requirements	US/Canada 208-230V, 50/60Hz, single phase, 50 amp - NEMA 6-50 Plug
Machine Dimensions	62"H x 91"W x 51"D (1575 mm x 2311 mm x 1397 mm)
Machine Weight	1850 lbs.
Shipping Dimensions	69"H x 99"W x 43"D (1613 mm x 2515 mm x 1083 mm)
Shipping Weight	2100 lbs. (953 kg)
Warranty	2 Year Limited. Extended warranty options available

ITEM#	DESCRIPTION	PRICE
64726	SEAL® 65 PRO MD LAMINATOR WITH SLITTER ASSEMBLY <i>Mechanical Requirement Sold Separately: 2 cfm compresses air @ 100psi</i>	\$